# televic

71.04.0162

# HSP 321 Single Ear Headset for Unite



### Description

The HSP 321 is a corded single ear headset designed for two-way communications with the Unite DECT Wireless Communication system. The headset allows the user to both listen and speak to a Unite TP or RP-T bodypack device simultaneously via a single connection. For example, it can be used for tour guide, intercom or wireless microphone applications.

The headset is immune to radio interference from DECT and mobile phones.

The length of the headband can be adjusted to suit the head shape of different users. The rotatable microphone boom can be flexibly adjusted so that the headset can fit different people.

### Features

- » Wideband audio transmission
- » Noise-cancelling electret condenser microphone
- » Flexible headband for optimum fit
- » Flexible microphone boom arm
- » Optimised for Unite bodypack devices
- » Soft, cleanable ear cushions made of artificial leather

## Specifications

| Headphone               |                               |
|-------------------------|-------------------------------|
| Frequency range         | 20 – 20,000 Hz                |
| Impedance               | 32 Ohm                        |
| Rated input power       | 10 mW                         |
| Ear cushions material   | Polyurethane                  |
| Ear cushions attachment | Detachable                    |
| Flexible mic boom       | Yes, adjustable 270°          |
| Interface               | 3.5 mm jack (angled, 4-pin)   |
| Interface standard      | CTIA                          |
| Cable length            | 90 cm                         |
| Weight                  | 54 g                          |
| Microphone              |                               |
| Туре                    | Electret condenser            |
| Directivity             | Directional, noise cancelling |
| Frequency range         | 100 – 8,000 Hz                |
| Min. sensitivity        | -40 dBV/Pa                    |
| Signal to noise ratio   | ≥ 60 dBA (1 kHz, 1 Pa)        |
| Operating voltage       | 1.5 – 5 V                     |
| Output impedance        | 2.2 kOhm                      |

#### **HQ Belgium**

+32 51 30 30 45 conference@televic.com https://www.televic.com/en/conference

Asia +86 21 61 48 01 23 conference@televic.com www.televic-conference.com.cn

#### f in 🎔 🖸 🖸

## France +33 3 74 09 52 76 conference-france@televic.com www.televic-conference.fr

United States +1 916 920 0901 conference-us@televic.com All information copyright Televic Conference, 2023. Televic reserves the right to change this document without notice.

Version 1.0